



The **First Name** in Turf Renovation™

# LAWNNAIRE® IV PLUS

**Whether you're a rental house, small lawn care contractor or homeowner, the Lawnnaire IV Plus has an application to suit your needs.**

This drum-style, self-propelled, high-speed precision turf aerator combines performance, durability and ease of use. Commercial-grade components like a solid steel axle and austemper-hardened steel coring tines ensure years of reliable performance in even the most rigorous environments. User-friendly features like the easy-to-operate, handle-mounted throttle and vibration-reducing grips make operation easy and comfortable. Thirty tines spread over a 19-inch swath offer a productive aeration rate of nearly 29,000 square feet per hour. Convenient transportation features such as a fold-down handle and removable weights for easier lifting cap off the long list of efficiency-building features you'll find in this versatile machine.



## SPECIFICATIONS

### POWER

Honda®

Engine Model . . . . . 4-cycle Honda® GX120; recoil start; on/off switch

Displacement . . . . . 7.2 cu in. (118 cc)

Fuel Capacity . . . . . 0.53 gal. (2 L)

Oil Capacity . . . . . 0.59 qt (0.56 L)

Briggs & Stratton®

Engine Model . . . . . 4-cycle Briggs & Stratton® Intek; recoil start; on/off switch; dual air cleaner; low-tone muffler

Displacement . . . . . 12.5 cu in. (205 cc)

Fuel Capacity . . . . . 0.73 gal. (2.8 L)

Oil Capacity . . . . . 0.63 qt (0.6 L)

### UNIT

Clutch . . . . . Belt tightener

Drive: Primary . . . . . 4L section V-belt

Drive: Tine & Drum . . . . . Single #40 nickel-plated chain

Tines . . . . . 0.75 in. (19 mm) diameter coring type formed from 0.08 in. (2 mm) hollow, austemper-hardened alloy steel; 30 tines per aerator

Lubrication . . . . . Not required; sealed ball bearings

Coring Depth . . . . . Up to 2.75 in. (70 mm)

Core Diameter . . . . . 0.75 in. (19 mm)

Aerating Width . . . . . 19 in. (483 mm)

Aeration Pattern . . . . . 3.75 in. x 7 in. (95 mm x 178 mm)

Holes per Sq Ft . . . . . Up to 9 sq ft

Productivity . . . . . Aerates up to 29,000 sq ft/hr (2,694 m<sup>2</sup>/hr)

Tires . . . . . (2) 8x2.25 semi-pneumatic w/ball bearings

### DIMENSIONS

Weight: Wet w/o Weights . . . . . 214 lb (97 kg)

Weight: Wet w/Weights . . . . . 255 lb (116 kg)

Weight: Wet w/Weights and Water in Drum . . . . . 298 lb (135 kg)

Width . . . . . 28 in. (711 mm)

Length . . . . . 53.5 in. (1,359 mm)

Height . . . . . 48.8 in. (1,240 mm); 30 in. (762 mm) w/handle folded

*Specifications subject to change without notice.*



The fold-down handle allows the machine to take up less space in transportation vehicles and rental houses.



Standard 3/4", austemper-hardened steel coring tines keep this durable machine out of the shop and out on the job.



Weights are easily and conveniently removable for easier lifting and quicker, less strenuous transportation.

# WWW.RYANTURF.COM