



The First Name in Turf Renovation™

TRACAIRE®

The Tracaire® 72-inch aerator is the only choice for athletic fields and other large, flat, high-traffic areas with compaction issues.

The hardened alloy steel tines aerate four inches down into even the most challenging surfaces, allowing deep-rooted grass to prosper in even the harshest conditions. An option of coring or spoon tines or slicing knives provides versatility, while cast iron tine wheels with sintered bushings add durability and reduce maintenance. Tow the Tracaire® aerator with a category "1" 3-point hitch and marvel at its resiliency – not to mention that of the resulting turf.



SPECIFICATIONS

UNIT

Power.....	Tractor mounted
Lubrication.....	Pressure grease fittings at pivot points and tine wheels
Hitch.....	Standard 3-point tractor hitch, category "1"
Aerating Wheel Axle.....	1.25 in. (32 mm) diameter
Aerating Wheels.....	12, cast iron with sintered bushings; pressure lubrication fitting; grooved for mounting aerating tines on both sides; each wheel weighs 75 lb (34 kg)
Tines.....	8 per wheel (96 total); standard one set 0.75 in. (19 mm) coring; wheels can be mounted with double set of tines, 16 per wheel (192 total)
Coring Depth.....	Up to 4 in. (102 mm)
Aerating Width.....	.72 in. (1,829 mm)
Aeration Pattern.....	6 in. x 6 in. (152 mm x 152 mm) with single tines; 3 in. x 3 in. (76 mm x 76 mm) with double tines
Holes per SqFt.....	Up to 9 sq ft (.84 m ²) with single tines; up to 18 sq ft (1.7 m ²) with double tines
Productivity.....	3 acres/hr (1.2 ha/hr) at 4 mph (6 km/hr)

DIMENSIONS

Weight.....	1,052 lb (477 kg)
Width.....	.78 in. (1,981 mm)
Length.....	.48 in. (1,219 mm)
Height.....	.24 in. (610 mm)

Specifications subject to change without notice.

TINES

- 515197* Tine, Coring 3/4" (19mm), Back Discharge, Thick Wall
- 515196 Tine, Coring 1/2" (13mm), Back Discharge, Thick Wall
- 520404 Tine, Spoon

KNIVES

- 521155 Deep Slicing Knife
- 515193 Shallow Slicing Knife

*Standard configuration



The cast iron aeration wheels have eight tines per wheel standard. Another eight tines can be installed on the wheel doubling the amount of material removed during coring.



Effortlessly connect the Tracaire to a wide variety of tractors with its durable three-point configuration.

WWW.RYANTURF.COM