

LAWNNAIRE® TOW-BEHIND AERATOR



TRUST RYAN®

Aerate more acres efficiently with the 36" Lawnnaire Tow-Behind, ideal for sports turf, recreational fields, and other mid-sized, one-to-five acre areas. Hooking up to your tractor, this tow-behind machine quickly and effortlessly aerates one-and-a-half acres per hour—helping you finish jobs ahead of schedule without sacrificing quality.

1. VERSATILE AERATION OPTIONS

Choose from 3/4 in. or 1/2 in. thick wall coring tines, 3/4 in. thick wall spooning tines, or shallow and deep slicing knives—all made from austemper-hardened steel and built built to penetrate to a depth of four inches.

2. CAST-IRON TINE WHEELS WITH SINTERED BUSHINGS

Avoid productivity-killing downtime with cast-iron tine wheels that feature sintered bushings and lubrication fittings for added durability and reduced maintenance needs.

3. INDEPENDENTLY MOUNTED TINES

Keep moving with independently mounted tine wheels that turn while tines are in the ground—allowing you to go where you need to go while maximizing productivity—for each and every job.



MANUAL, HYDRAULIC, AND ELECTRIC LIFT OPTIONS



ADD EIGHT ADDITIONAL TINES PER WHEEL



FOR MORE INFORMATION, VISIT RYANTURF.COM



LAWNAIRE® TOW-BEHIND SPECIFICATIONS

Frame	1.5 in. (38 mm) sq x 0.1875 in. (5 mm) wall tube
Hitch	Clevis and pin type
Aerating Wheel Axle	1.25 in. (32 mm) diameter
Transport Wheel Axle	0.75 in. (19 mm) diameter
Aerating Wheels	<ul style="list-style-type: none"> • Cast iron with sintered bushings • Pressure lubrication fitting • Grooved for mounting aerating tines on both sides • Each wheel weighs 75 lb (34 kg)
Tines (# of)	<ul style="list-style-type: none"> • 8 per wheel (48 total) • One set 0.75 in. (19 mm) diameter coring tines standard • Tines are formed from austemper-hardened alloy steel • Wheels can be mounted with double tines, 16 per wheel (96 total)
Coring Depth	Up to 5 in. (127 mm)
Aerating Width	36 in. (914 mm)
Aeration Pattern	<ul style="list-style-type: none"> • 6 in. x 6 in. (152 mm x 152 mm) with single tines • 3 in. x 3 in. (76 mm x 76 mm) with double tines
Weight	500 lb (227 kg)
Width	46 in. (1.2 m)
Length	68.5 in. (1.7 m)
Height	31 in. (787 mm)
Productivity	Up to 1.5 acres/hr (0.6 ha/hr) at 4 mph (6 km/hr)
Towing Speed	10 mph (16 km/hr) max
Transport Lift	Wheels are pivotable about extended axle shaft using removable lever or 700 psi hydraulic lift
Transport Tires	4.10/3.50-4, 2-ply, semi-pneumatic tires with ball bearings
Options*	Hydraulic, electric, or manual lift
Power	Tractor-draw
Lubrication	Pressure grease fittings at tine wheels and wheels

FOR MORE INFORMATION,
VISIT RYANTURF.COM

One Bobcat Lane | Johnson Creek, WI 53038-0469

For more information about RYAN® products, visit your RYAN® dealer today. For the location of the dealer nearest you, call 866-469-1242 or visit www.ryanturf.com.

©2022 Clark Equipment Co. All Rights Reserved.



TRUST RYAN®